

AGRIMAX FORTIS - Technical Specifications



Description

AGRIMAX FORTIS is your reliable partner for all preparation, soil tillage and haulage operations. Designed to equip the latest, most modern and most powerful tractors, AGRIMAX FORTIS allows you to carry very high loads reaching up to 65 km/h (40 MPH). It ensures outstanding traction along with top handling and best comfort for a perfect driving experience. The tire has been designed with a reinforced nylon casing for enhanced productivity in the fields preserving the soil thanks to reduced compaction.

UM

International Standard

Construction



RADIAL

Machinery

Agriculture: Tractor

Version	SPECIAL
Type	TL
Tyre Size	650/85 R 38
LI/SS	173 D/176 A8

Dimensions International Standard

Section Width (mm)	675
Overall Diameter (mm)	2071
Static Loaded Radius (mm)	935
Rolling Circumference (mm)	6184
SRI (mm)	975
Rim Rec	DW 23 B
Rim Alt	DW 21 B ; DW 20 B
ECE	E4-106R-001426
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	3120	3640	4095	4550	5005	5395	5980	6500
50	3280	3825	4300	4780	5260	5665	6280	6825
40	3410	3980	4475	4970	5470	5895	6535	7100
30	3590	4190	4710	5235	5760	6205	6880	7475
10 LT	4185	4880	5490	6100	6710	7230	8015	8710
10 HT	3590	4190	4710	5235	5760	6205	6880	7475

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..