

## AGRIMAX RT 657 - Technical Specifications



### Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	320/65 R 16
LI/SS	117 D/120 A8

## Dimensions International Standard

Section Width (mm)	319
Overall Diameter (mm)	822
Static Loaded Radius (mm)	366
Rolling Circumference (mm)	2466
SRI (mm)	390
Rim Rec	W 10
Rim Alt	W 9 ; W 11
ECE	E4-106R-001815
TRA Code	R1W

## Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	605	710	810	900	990	1070	1185	1285
50	635	745	855	945	1040	1125	1245	1350
40	660	770	885	980	1080	1165	1290	1400
30	700	815	935	1040	1140	1230	1365	1480
10 LT	815	950	1090	1210	1330	1435	1590	1725
10 HT	700	815	935	1040	1140	1230	1365	1480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..