

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

US Standard

Construction



Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	480/80 R 46 (18.4 R 46)
LI/SS	164 A8/B

Dimensions US Standard

Usa code	94040537
Section Width (inch)	18.9
Overall Diameter (inch)	76.2
Static Loaded Radius (inch)	35.2
Rolling Circumference (inch)	231.1
Rim Rec	DW 16 A; W 16 A; DD 16
Rim Alt	W 16 L; DD 16 L; DW 16 L
ECE	E4-106R-000798
TRA Code	R1W

Load capacity (lbs)

mph / psi	12	15	17	20	23	29	35	41	46
30	5060	5810	6560	7310	8060	8720	9350	10250	11000
25	5060	5810	6560	7310	8060	8720	9350	10250	11000
20	5420	6230	7020	7830	8630	9340	10030	10970	11790
5 LT	6790	7790	8800	9800	10800	11680	12550	13730	14770
5 HT	5420	6230	7020	7830	8630	9340	10030	10970	11790

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 01:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..