

AGRIMAX RT 855 - Technical Specifications



Description

AGRIMAX RT 855 provides excellent traction and comfort properties. Mainly designed for soil tillage and both field and road transport, some sizes are also suitable for spraying, and vineyard harvesting. AGRIMAX RT 855 has excellent self-cleaning features that allow for a quick change from field operations to road usage.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	520/85 R 50 (20.8 R 50)
LI/SS	165 A8/B

Dimensions International Standard

Section Width (mm)	516
Overall Diameter (mm)	2154
Static Loaded Radius (mm)	992
Rolling Circumference (mm)	6472
SRI (mm)	1025
Rim Rec	DW 16L
Rim Alt	DW 18 L
ECE	E11-106R-004895
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
50	2425	2785	3195	3605	4020	4430	4845	5150
40	2425	2785	3195	3605	4020	4430	4845	5150
30	2595	2980	3420	3865	4305	4745	5185	5515
10 LT	3250	3730	4285	4835	5390	5940	6495	6905
10 HT	2595	2980	3420	3865	4305	4745	5185	5515

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..