

AGRIMAX RT 955 - Technical Specifications



Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	270/80 R 36
LI/SS	134 A8/B

Dimensions US Standard

Usa code	94067046
Section Width (inch)	10.8
Overall Diameter (inch)	53
Static Loaded Radius (inch)	24.8
Rolling Circumference (inch)	161
Rim Rec	W9
Rim Alt	W8; W10
ECE	E11-106R-006758
TRA Code	R1

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35	41	46	52	58
30	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
25	1640	1920	2200	2480	2770	3000	3330	3510	3840	4170	4440	4670
20	1750	2060	2360	2660	2950	3210	3560	3760	4110	4460	4760	5000
5	2460	2880	3300	3730	4140	4500	4980	5260	5750	6250	6670	7010

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 11:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..