

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great self-cleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/70 R 30
LI/SS	141 A8 / 141 B

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1478
Static Loaded Radius (mm)	660
Rolling Circumference (mm)	4396
SRI (mm)	675
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-009050

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1420	1650	1880	2115	2345	2575
40	1420	1650	1880	2115	2345	2575
30	1520	1770	2015	2265	2515	2760
10 LT	1905	2215	2525	2835	3145	3455
10 HT	1520	1770	2015	2265	2515	2760

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/02/2025 23:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..