

AGRIMAX V-FLECTO - Technical Specifications



Description

AGRIMAX V-FLECTO is BKT's response to the challenging demand of both technology and performance for high-power tractors. This tire is perfect for soil tillage and haulage applications thanks to reduced soil compaction and self-cleaning properties. With the exclusive VF technology, AGRIMAX V-FLECTO can carry heavy loads with a lower inflating pressure compared to standard and IF tires, reaching high speeds. It also features the Narrow Rim Option that allows mounting standard rims on the tire. BKT has designed this tire with optimized geometry to enhance driving comfort both in the fields and on the road reducing fuel consumption.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: High-Power Tractor

Version	STANDARD
Type	TL
Tyre Size	VF 600/70 R 34 NRO
LI/SS	170 D

Dimensions International Standard

Section Width (mm)	603
Overall Diameter (mm)	1704
Static Loaded Radius (mm)	740
Rolling Circumference (mm)	5040
SRI (mm)	800
Rim Rec	DW 21 B
Rim Alt	DW 20 B
Narrow Rim option	DW 18 B
ECE	E11-106R-008813
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0
70	2730	3165	3600	4095	4530	4965	5460
From 65 to 40	3000	3480	3960	4500	4980	5460	6000
30	3060	3545	4035	4590	5075	5565	6120
20	3120	3615	4115	4680	5175	5675	6240
10	3300	3825	4355	4950	5475	6005	6600
*Upto 10 Cyc with front loader	4200	4870	5540	6300	6970	7640	8400
10 HT	3060	3545	4035	4590	5075	5565	6120

* *For Upto 10 Cyc with front loader application inflation pressure to be increased by 0.8 bar.

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..