

## AS 504 - Technical Specifications



### Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	12.5/80 - 18
LI/SS DRIVE WHEEL	138 A8
LI/SS FREE ROLLING	150 A8

## Dimensions International Standard

Ply Rating	18
Section Width (mm)	308
Overall Diameter (mm)	987
Static Loaded Radius (mm)	438
Rolling Circumference (mm)	2892
SRI (mm)	475
Rim Rec	W 9
Rim Alt	9 ; 11
ECE	E11-106R-004348

## Load capacity (Kg)

	km/h / bar	5.50
	10 FR	4690
	25 FR	3985
	30 FR	3750
	40 FR	3350
	10 DW	3305
	25 DW	2810
	30 DW	2645
	40 DW	2360

Printed on 02/07/2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..