

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	16.0/70 - 20
LI/SS DRIVE WHEEL	135 A8
LI/SS FREE ROLLING	147 A8

Dimensions International Standard

Ply Rating	10
Section Width (mm)	418
Overall Diameter (mm)	1097
Static Loaded Radius (mm)	487
Rolling Circumference (mm)	3214
SRI (mm)	525
Rim Rec	13
Rim Alt	12 SDC ; 14 ; 13 SDC
ECE	E4-106R-001875

Load capacity (Kg)

	km/h / bar	2.50
	10 FR	4305
	25 FR	3660
	30 FR	3445
	40 FR	3075
	10 DW	3050
	25 DW	2595
	30 DW	2440
	40 DW	2180

Printed on 02/07/2024 18:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..