

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer
Industrial: Telehandler

Version	STANDARD
Type	TT
Tyre Size	27 X 10 - 15.3
LI/SS DRIVE WHEEL	95 A8
LI/SS FREE ROLLING	107 A8

Dimensions US Standard

Usa code	94027439
Ply Rating	8
Section Width (inch)	10.2
Overall Diameter (inch)	27.4
Static Loaded Radius (inch)	12.5
Rolling Circumference (inch)	81.5
Rim Rec	9.00
ECE	E4-106R-002324

Load capacity (lbs)

mph / psi	45
5 FR	3010
15 FR	2560
20 FR	2400
25 FR	2150
5 DW	2130
15 DW	1810
20 DW	1710
25 DW	1520

Printed on 02/07/2024 18:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..