

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	420/55 - 17
LI/SS DRIVE WHEEL	133 A8
LI/SS FREE ROLLING	145 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	430
Overall Diameter (mm)	910
Static Loaded Radius (mm)	407
Rolling Circumference (mm)	2712
Rim Rec	13.00
ECE	E11-106R-003302

Load capacity (Kg)

	km/h / bar	3.50
	10 FR	4060
	25 FR	3450
	30 FR	3250
	40 FR	2900
	10 DW	2885
	25 DW	2450
	30 DW	2305
	40 DW	2060

Printed on 02/07/2024 18:14

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..