

AS 504 - Technical Specifications



Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Telehandler • Field Trailer
Industrial: Telehandler

Version	STANDARD
Type	TT
Tyre Size	6.00 - 16
LI/SS DRIVE WHEEL	83 A8
LI/SS FREE ROLLING	95 A8

Dimensions US Standard

Usa code	94019168
Ply Rating	6
Section Width (inch)	6.5
Overall Diameter (inch)	28.9
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	86.2
Rim Rec	4.00 E
Rim Alt	4.50 E ; 4½ K
ECE	E4-106R-002836

Load capacity (lbs)

mph / psi	41
5 FR	2130
15 FR	1810
20 FR	1710
25 FR	1520
5 DW	1500
15 DW	1270
20 DW	1200
25 DW	1070

Printed on 04/07/2024 18:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..