

# AS 504 - Technical Specifications



## Description

AS 504 is an agro-industrial tire mainly designed for soil tillage, implement and material-handling operations. This tire, which features excellent self-cleaning properties and increased grip, is suitable for field trailers and telehandlers. AS 504 is available in several versions to meet specific end-user requirements: an "HD" version with a special cut-and-chip resistance compound, while the "special" version has a reinforced casing that ensures a longer tire life.

## UM

US Standard

## Construction

 BIAS

## Machinery

Agriculture: Telehandler • Field Trailer

Industrial: Telehandler

Version	HD
Type	TT
Tyre Size	6.5/80 - 12
LI/SS DRIVE WHEEL	80 A8
LI/SS FREE ROLLING	93 A8

## Dimensions US Standard

Usa code	94043828
Ply Rating	6
Section Width (inch)	6.7
Overall Diameter (inch)	23.9
Static Loaded Radius (inch)	11.1
Rolling Circumference (inch)	72.3
Rim Rec	5 J
Rim Alt	5 JA
ECE	E11-106R-004088

## Load capacity (lbs)

mph / psi	52
5 FR	2010
15 FR	1710
20 FR	1610
25 FR	1430
5 DW	1390
15 DW	1180
20 DW	1110
25 DW	990

Printed on 02/07/2024 18:05

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..