

AW 909 - Technical Specifications



Description

AW 909 has been developed for soil tillage, hay harvesting and transport applications with implement machinery, trailers and balers. It is ideal for modern farming both on and off the road.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	10.0/75 - 15.3
LI/SS FREE ROLLING	135 A8

Dimensions US Standard

Usa code	94010462
Ply Rating	18
Section Width (inch)	10.8
Overall Diameter (inch)	29.9
Static Loaded Radius (inch)	13.5
Rolling Circumference (inch)	87.7
Rim Rec	9.00
ECE	E4-106R-001880

Load capacity (lbs)

mph / psi	103
5 FR	6720
15 FR	5720
20 FR	5380
25 FR	4810

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..