

BOGMAX - Data Sheet



Description

BOGMAX has been specially designed for all-terrain applications. The very deep tread pattern ensures excellent traction whereas the sidewall protectors reduce impacts and possible damages. BOGMAX is a 6-ply-rated tire with M+S technology - perfect for sport performance in every condition.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: ATV

SIZE	Version	LI/SS	PR	RIM REC	RIM ALT	SW	OD	Type
AT 30 X 10 - 14	STANDARD	58 F	6	7.0 AT	7.5 AT ; 8.0 AT	260	760	TL
AT 32 X 10 - 14	STANDARD	62 F	6	8.0 AT	8.5 AT	250	810	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..