

D 404 - Technical Specifications



Description

D 404 is a road-oriented tire ideal for transport applications with trailers and light trucks. An excellent grip on the road along with regular wear turns into extra durability.

UM

International Standard

Construction

BIAS

Machinery

Agriculture: Light Truck • Trailer

Version	STANDARD
Туре	тт
Tyre Size	8.25 - 16

Dimensions International Standard

Ply Rating	14
Section Width (mm)	238
Overall Diameter (mm)	858
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E4-54R-0024095

Load capacity (Kg)

km/h / bar	6.90
100 LS	1745
100 LD	1650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 13:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..