

# EARTHMAX SR 22 AS - Technical Specifications



## Description

EARTHMAX SR 22 AS (E-2\*\*/G-2\*/L-2\*\*) is an All Steel radial tire specially designed for graders, small loaders and trucks operating on ice and snow ensuring also optimum performance in all-season conditions.

The extraordinary tread design features deep sipes and a four-block pattern. Made of unique winter compounds, it provides superior braking performance in icy or snowy conditions and avoids stone trapping during all-season usage.

The low void ratio and wide footprint of EARTHMAX SR 22 AS stand for excellent traction and stability with even wear, and a long tread life.

## UM

US Standard

## Construction

 RADIAL

## Machinery

OTR: Grader • Loader

Version	CUT RESISTANT COMPOUND
Type	TL
Tyre Size	20.5 R 25
LI/SS	177 B/161 A8/193 A2

## Dimensions US Standard

Usa code	94073160
Overall Width (inch)	20.9
Overall Diameter (inch)	58.8
Static Loaded Radius (inch)	25.2
Rolling Circumference (inch)	170.2
Rim Rec	17.00/2.0
Star Rating	**/**/**
TRA Code	E2/G2/L2

## Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91	94
30	-	-	-	-	-	-	-	-	12800	13600	14300	14800	15200	16100	-	-	-	-	-
25	5360	6150	6950	7600	8550	9100	9650	10200	-	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	21500	22000	22700	24000	24700	25400

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:16

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..