

EARTHMAX SR 22 AS - Technical Specifications



Description

EARTHMAX SR 22 AS (E-2**/G-2*/L-2**) is an All Steel radial tire specially designed for graders, small loaders and trucks operating on ice and snow ensuring also optimum performance in all-season conditions.

The extraordinary tread design features deep sipes and a four-block pattern. Made of unique winter compounds, it provides superior braking performance in icy or snowy conditions and avoids stone trapping during all-season usage.

The low void ratio and wide footprint of EARTHMAX SR 22 AS stand for excellent traction and stability with even wear, and a long tread life.

UM

US Standard

Construction

💥 RADIAL

Machinery

OTR: Grader • Loader

Version	CUT RESISTANT COMPOUND
Туре	TL
Tyre Size	23.5 R 25
LI/SS	185 B/170 A8 /201 A2

Dimensions US Standard

Usa code	94073405
Overall Width (inch)	24
Overall Diameter (inch)	63.5
Static Loaded Radius (inch)	27.9
Rolling Circumference (inch)	191.5
Rim Rec	19.50/2.5
Star Rating	**/*/**
TRA Code	E2/G2/L2

Load capacity (lbs)

mph / psi	18	22	25	29	33	36	40	44	58	62	65	69	73	76	80	83	87	91	94
30	-	-	-	-	-	-	-	-	16500	17100	18200	18700	19800	20400	-	-	-	-	-
25	6950	7850	8800	9900	10700	11700	12300	13200	-	-	-	-	-	-	-	-	-	-	-
5	-	-	-	-	-	-	-	-	-	-	-	-	-	27600	28300	29100	30000	30900	32000

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:49

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..