



EARTHMAX SR 45 H2 - Data Sheet



Description

EARTHMAX SR 45 H2 is an All Steel radial tire specifically designed for rigid haul trucks. The E-4 tread depth and the unique tread pattern ensure excellent wear minimizing vibration and noise. EARTHMAX SR 45 H2 is ideal for all operations requiring traction and stability. The All Steel casing provides excellent resistance to snags and punctures and a long service life. Available in standard, heat-resistant and cut-resistant compounds.

UM

International Standard

Construction

 RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TKPH
24.00 R 35	CUT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	333
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	333
24.00 R 35	HEAT RESISTANT COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	435
24.00 R 35	HEAT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	435
24.00 R 35	STANDARD COMPOUND	E4	***	212 B	17.00/3.5	---	660	2180	978	6597	TL	390
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5	--	660	2180	978	6597	TL	390

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:26

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..