

## EARTHMAX SR 468 - Data Sheet



### Description

EARTHMAX SR 468 is an All Steel radial tire specially designed for rigid haul trucks. Its unique tread design with special tread compounds makes it perfect for hard, rocky and tough mining conditions. Its tread lug blocks with circumferential grooves and intertwined blocks ensures effective heat dissipation. Also, the sturdy square shoulder assist in ejecting loose stones to protect the tire from injury. EARTHMAX SR 468 is developed using BKT's cutting-edge technology to carry heavy loads, deliver longer service life and provide resistance to rock cuts and punctures.

### UM

US Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	TMPH
37.00 R 57	CUT RESISTANT COMPOUND	94069354	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	497
37.00 R 57	HEAT RESISTANT COMPOUND	94069347	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	699
37.00 R 57	STANDARD COMPOUND	94069361	E4	**	245 B	27.00/6.0	29.00/6.0	40.6	134.8	59.8	406.1	TL	582
40.00 R 57	CUT RESISTANT COMPOUND	94068845	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	548
40.00 R 57	HEAT RESISTANT COMPOUND	94067381	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	774
40.00 R 57	STANDARD COMPOUND	94068852	E4	**	250 B	29.00/6.0	32.00/6.0	44.3	140.7	62.8	421.3	TL	651
46/90 R 57	CUT RESISTANT COMPOUND	94070589	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	565
46/90 R 57	HEAT RESISTANT COMPOUND	94070596	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	798
46/90 R 57	STANDARD COMPOUND	94070602	E4	**	252 B	29.00/6.0	32.00/6.0	44.9	140.7	62.6	425.2	TL	671
50/80 R 57	CUT RESISTANT COMPOUND	94075164	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	651
50/80 R 57	HEAT RESISTANT COMPOUND	94075157	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	918
50/80 R 57	STANDARD COMPOUND	94074228	E4	**	257 B	32.00/6.0	34.00/6.0 , 29.00/6.0	47.4	142.1	62.9	428	TL	774

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 06:22

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..