

EARTHMAX SR 475 - Data Sheet



Description

EARTHMAX SR 475 is an all steel radial tire specially designed for Rigid Dump Trucks. It is ideal for hard and rocky operations especially with long hauls. The unique tread design generate lower heat in hot climate and provides excellent traction. Its strong all steel casing and belts provide great stability and resistant to snags and punctures. EARTHMAX SR 475 has been developed with squared shoulder that ensures excellent maneuverability and handling, maximizing the ground contact.

UM

International Standard

Construction

RADIAL

Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Type	TKPH
18.00 R 33	CUT RESISTANT COMPOUND	E4	**	191 B	13.00/2.5		490	1860	860	5721	TL	265
18.00 R 33	CUT RESISTANT COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	265
18.00 R 33	STANDARD COMPOUND	E4	***	195 B	13.00/2.5		490	1860	860	5721	TL	292
24.00 R 35	CUT RESISTANT COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	355
24.00 R 35	STANDARD COMPOUND	E4	**	209 B	17.00/3.5		654	2160	971	6589	TL	422

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..