

EM 936 LOADER SPECIAL - Data Sheet



Description

EM 936 LOADER SPECIAL has been specially designed for telehandlers in loading applications. It features outstanding riding comfort and enhanced self-cleaning properties. It also ensures a high level of handling comfort and provides excellent traction even under heavy-duty service conditions.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Loader • Telehandler

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | OW | OD | SLR | RC | Type |
|-------------------------------|----------|----------|-------|----|---------|---------|-----|------|-----|------|------|
| 16.0/70 - 20 (405/70 - 20) | STANDARD | E2 | 149 B | 14 | 13 SDC | 13 | 405 | 1090 | 480 | 3295 | TL |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 02:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..