

FARM 2000 PLUS - Technical Specifications



Description

FARM 2000 PLUS is an agriculture tire featuring a higher number of lugs for better performance in the fields. The deep tread provides an extended tire life and great traction, whereas the superior tread compound ensures better cut and chip resistance. FARM 2000 PLUS shows excellent self-cleaning features and specially designed lug angles making the tire particularly suitable for field and haulage applications.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	SPECIAL
Type	TT
Tyre Size	16.9 - 28
LI/SS	143 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1435
Static Loaded Radius (mm)	657
Rolling Circumference (mm)	4311
Rim Rec	W 15 L
Rim Alt	W 14 L
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2725

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..