



FARM 2000 - Data Sheet



Description

The FARM 2000 tire is suitable on tractors for soil tillage applications. It has been designed with a special cut-and-chip resistant compound to ensure better durability. Thanks to its strong casing, FARM 2000 offers high load capacity. It also provides great traction and self-cleaning properties.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	USACode	TRA Code	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
260/70 - 15.3	STANDARD	94035366			114 A8	126 A8		9.00		10.4	30.5	13.7	90.3	TL	E11-106R-003516
300/80 - 15.3	STANDARD	94034673			120 A8	132 A8		9.00		11.8	35	15.3	102.7	TL	E11-106R-003517
250/80 - 16	STANDARD	94040278	R1		113 A8	125 A8		W 8	W 7 ; W 9 ; W 8 L	9.4	32.3	14.5	95.6	TT	E11-106R-003518
250/80 - 16	STANDARD	94033614	R1		113 A8	125 A8		W 8	W 7 ; W 9 ; W 8 L	9.4	32.3	14.5	95.6	TL	E11-106R-003518
250/80 - 18	STANDARD	94040285	R1		115 A8	127 A8		W 8	W 7 ; W 9	9.4	34.3	15.5	105.5	TT	E11-106R-003519
250/80 - 18	STANDARD	94040292	R1		115 A8	127 A8		W 8	W 7 ; W 9	9.4	34.3	15.5	105.5	TL	E11-106R-003519
8 - 18	STANDARD	94045068	R1	81 A8			4	W 6		7.7	33.1	15.4	96.8	TT	E11-106R-004084
8 - 18	STANDARD	94049738	R1	90 A8			6	W 6		7.7	33.1	15.5	100	TT	E11-106R-002960
9.5 - 18	STANDARD	46178	R1	101 A8			8	W 8	W 7	9.5	35.4	16.5	108.3	TT	E11-106R-0010140
8.3 - 20	STANDARD	94045051	R1				4	W 7		8.3	35.2	17	106.9	TT	E11-106R-004369
8.3 - 20	STANDARD	94045259	R1				6	W 7		8.3	35.2	17	106.9	TT	E11-106R-002957
9.5 - 20	STANDARD	94076307	R1	103 A8			8	W 8	W 7	9.5	37.2	17.5	114.6	TT	E11-106R-0010141
8.3 - 24	STANDARD	94047901	R1				6	W 7	W 6	8.3	39.2	18.6	119.4	TT	
8.3 - 24	STANDARD	94051908	R1	101 A8			8	W 7	W 6	8.3	39.2	18.6	119.4	TT	E11-106R-004094
12.4 - 28	STANDARD	94002856	R1	120 A8			8	W 11	W 9 ; W 10	12.6	50.7	23.7	156.3	TT	
12.4 - 28	STANDARD	94002863	R1	121 A8			10	W 11	W 9 ; W 10	12.6	50.7	23.7	156.3	TT	E11-106R-005964
12.4 - 28	STANDARD	94002870	R1	122 A8			12	W 11	W 9 ; W 10	12.6	50.7	23.7	156.3	TT	E11-106R-005965
13.6 - 28	SPECIAL	94060641	R1	124 A8			12	W 12	W 11	13.6	52.6	24.5	160.6	TT	E11-106R-003002
13.6 - 28	STANDARD	94002917	R1	124 A8			12	W 12	W 11	13.6	52.6	24.5	160.6	TT	E11-106R-003002
13.6 - 28	STANDARD	94002894	R1	122 A8			8	W 12	W 11	13.6	52.6	24.5	160.6	TT	E11-106R-004373
13.6 - 28	STANDARD	94002900	R1	123 A8			10	W 12	W 11	13.6	52.6	24.5	160.6	TT	E11-106R-004374
14.9 - 28	STANDARD	94031764	R1	130 A8			12	W 13	W 11 ; W 12	15.2	54.1	25	165.1	TT	E11-106R-005966
14.9 - 28	STANDARD	94041824	R1	132 A8			14	W 13	W 11 ; W 12	15.2	54.1	25	165.1	TT	E11-106R-005968

14.9 - 28	STANDARD	94033515	R1	126 A8	8	W 13	W 11; W 12	15.2	54.1	25	165.1	TT	E11- 106R- 004375
14.9 - 28	STANDARD	94032853	R1	128 A8	10	W 13	W 11; W 12	15.2	54.1	25	165.1	TT	E11- 106R- 005967
16.9 - 28	HD	94041312	R1	131 A8	8	W 15 L	W 14 L	16.9	55.9	25.9	171.3	TT	E11- 106R- 004378
16.9 - 28	STANDARD	94002924	R1	139 A8	12	W 15 L	W 14 L	16.9	55.9	25.9	171.3	TT	E11- 106R- 003627
18.4 - 30	STANDARD	94044382	R1	147 A8	14	W 16 L		18.5	61.4	28.2	188	TT	E11- 106R- 004525

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..