

FL 252 - Technical Specifications



Description

FL 252 is a tire suitable for hay harvesting applications with rotor rakes/tedders as well as for logistic operations using forklifts. This tire provides excellent durability while the specific tread pattern ensures maximum stability during lifting operations.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Rotor Rake / Tedder
Industrial: Forklift

| | |
|-----------|----------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 6.00 - 9 |

Dimensions US Standard

| | |
|-------------------------|----------|
| Usa code | 94006854 |
| Ply Rating | 10 |
| Section Width (inch) | 6.7 |
| Overall Diameter (inch) | 21.7 |
| Rim Rec | 4.00 E |

Load capacity (lbs)

| | mph / psi | 123 |
|--------------------|-----------|------|
| 15 LOAD WHEEL | | 3780 |
| 15 STEER WHEEL | | 2910 |
| 5 OTHER VEHICLES | | 3780 |
| 15 OTHER VEHICLES | | 2910 |
| STATIC SIDE LOADER | | 4400 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:25

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..