



## I - 1 - Data Sheet



### Description

I-1 has been designed for field and road transport as well as for soil tillage operations with implements and trailers. I-1 is a high-speed tire that optimizes travel times so that you can focus on your core business. The special tread design ensures a long service life also in harsh conditions and if there is stubble in the fields.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Trailer

SIZE	Version	USACode	TRA Code	LI/SS	LI/SS FREE ROLLING	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	TMPH	ECE
11L - 14 SL	STANDARD	94035359	I1	112 D		8	8.00	8 KB	10.1	29.6	13.1	86.9	TL	0	E11-106R-004268
9.5L - 14 SL	STANDARD	94006113	I1	111 D		8	7.00	8 KB	9.3	29.3	12.8	84.8	TT	0	E11-106R-004571
9.5L - 14 SL	STANDARD	94006120	I1	111 D		8	7.00	8 KB	9.3	29.3	12.8	84.8	TL	0	E11-106R-004571
11L - 15 SL	STANDARD	94005895	I1	118 D		10	8 LB	10 LB	10.6	30.3	13.5	88.8	TT	0	E11-106R-004547
11L - 15 SL	STANDARD	94005901	I1	118 D		10	8 LB	10 LB	10.6	30.3	13.5	88.8	TL	0	E11-106R-004547
11L - 15 SL	STANDARD	94026197	I1	121 D		12	8 LB	10 LB	10.6	30.3	13.5	88.8	TL	0	E11-106R-003521
11L - 15 SL	STANDARD	94005864	I1	113 D		8	8 LB	10 LB	10.6	30.3	13.5	88.8	TT	0	E11-106R-003350
11L - 15 SL	STANDARD	94005871	I1	113 D		8	8 LB	10 LB	10.6	30.3	13.5	88.8	TL	0	E11-106R-003350
11L - 15 SL	STUBBLE RESISTANT	94044801	I1	113 D		8	8 LB	10 LB	10.6	30.3	13.5	88.8	TL	0	
11L - 15 SL	STUBBLE RESISTANT	94044818	I1	121 D		12	8 LB	10 LB	10.6	30.3	13.5	88.8	TL	0	E11-106R-004575
12.5L - 15 SL	STANDARD	94005994	I1			10	10 LB		12.2	32.3	14.3	94.6	TL	0	E11-106R-004578
12.5L - 15 SL	STANDARD	94006021	I1			12	10 LB		12.2	32.3	14.3	94.6	TT	0	E11-106R-003371
12.5L - 15 SL	STANDARD	94006038	I1			12	10 LB		12.2	32.3	14.3	94.6	TL	0	E11-106R-003371
12.5L - 15 SL	STANDARD	94005963	I1	119 D		8	10 LB		12.2	32.3	14.3	94.6	TT	0	E11-106R-004577
12.5L - 15 SL	STANDARD	94005970	I1	119 D		8	10 LB		12.2	32.3	14.3	94.6	TL	0	E11-106R-004577
12.5L - 15 SL	STANDARD	94005987	I1	123 D		10	10 LB		12.2	32.3	14.3	94.6	TT	0	E11-106R-004578
12.5L - 15 SL	STUBBLE RESISTANT	94044825	I1			12	10 LB		12.2	32.3	14.3	94.6	TL	0	E11-106R-004580
6.70 - 15 SL	STANDARD	94045204	I1	97 D		6	4½ KB	5 KB	6.8	28	12.6	81.9	TL	0	E11-106R-003443
6.70 - 15 SL	STANDARD	94006083	I1	97 D		6	4½ KB	5 KB	6.8	28	12.6	81.9	TT	0	E11-106R-003443
6.70 - 15 SL	STANDARD	94005734	I1	102 D		8	4½ KB	5 KB	6.8	28	12.6	81.9	TT	0	E11-106R-005266
7.60 - 15 SL	STANDARD	94056996	I1	106 D		8	5.50	6 LB	7.6	28.9	12.9	84.7	TL	0	
7.60 - 15 SL	STANDARD	94048458	I1	110 D		10	5.50	6 LB	7.6	28.9	12.9	84.7	TL	0	E11-106R-003520
7.60 - 15 SL	STANDARD	94039838	I1	100 D		6	5.50	6 LB	7.6	28.9	12.9	84.7	TT	0	

7.60 - 15 SL	STANDARD	94039845	I1	106 D	8	5.50	6 LB	7.6	28.9	12.9	84.7	TT	0	
7.60 - 15 SL	STANDARD	94034819	I1	110 D	10	5.50	6 LB	7.6	28.9	12.9	84.7	TT	0	E11-106R-003520
9.5L - 15 SL	STANDARD	94028481	I1	105 D	6	7.00	8 LB	9.5	30.1	13.4	88.3	TT	0	E11-106R-003444
9.5L - 15 SL	STANDARD	94006144	I1	112 D	8	7.00	8 LB	9.5	30.1	13.4	88.3	TT	0	E11-106R-003445
9.5L - 15 SL	STANDARD	94006151	I1	112 D	8	7.00	8 LB	9.5	30.1	13.4	88.3	TL	0	E11-106R-003445
9.5L - 15 SL	STANDARD	94006175	I1	121 D	12	7.00	8 LB	9.5	30.1	13.4	88.3	TL	0	E11-106R-003370
9.5L - 15 SL	STUBBLE RESISTANT	94044498	I1	112 D	8	7.00	8 LB	9.5	30.1	13.4	88.3	TL	0	E11-106R-003363
9.5L - 15 SL	STUBBLE RESISTANT	94045174	I1	121 D	12	7.00	8 LB	9.5	30.1	13.4	88.3	TL	0	E11-106R-003383
10.0/75 - 15.3	STANDARD	94065202	I1	118 D	12	9.00		10.6	30.1	0	0	TT	0	E11-106R-006267
10.0/75 - 15.3	STANDARD	94065219		118 D	12	9.00		10.6	30.1	0	0	TL	0	E11-106R-006267
11L - 16 SL	STANDARD	94005925	I1		8	8 LB	10 LB ; W 8 L	10.6	31.3	14	91.7	TT	0	E11-106R-006675
11L - 16 SL	STANDARD	94005949	I1		10	8 LB	10 LB ; W 8 L	10.6	31.3	14	91.7	TT	0	E11-106R-004286
11L - 16 SL	STANDARD	94031405	I1		12	8 LB	10 LB ; W 8 L	10.6	31.3	14	91.7	TT	0	E11-106R-004287
12.5L - 16 SL	STANDARD	94041411	I1		12	10 LB	W 10 L	12.2	33.3	14.7	97.5	TL	0	E11-106R-004294
12.5L - 16 SL	STANDARD	94006045	I1		8	10 LB	W 10 L	12.2	33.3	14.7	97.5	TT	0	E11-106R-005101
12.5L - 16 SL	STANDARD	94005697	I1		10	10 LB	W 10 L	12.2	33.3	14.7	97.5	TT	0	E11-106R-004293
12.5L - 16 SL	STANDARD	94006069	I1		12	10 LB	W 10 L	12.2	33.3	14.7	97.5	TT	0	E11-106R-004294
12.5L - 16 SL	STUBBLE RESISTANT	94048205	I1		14	10 LB	W 10 L	12.2	33.3	14.7	97.5	TL	0	E11-106R-004296
7.50 - 16 SL	SPECIAL	94030910	I1		8	5.50 F	6 LB	8.1	30.9	13.8	90.6	TT	0	
7.50 - 16 SL	SPECIAL	94041534	I1		10	5.50 F	6 LB	8.1	30.9	13.8	90.6	TT	0	
7.50 - 16 SL	STANDARD	94006090	I1		8	5.50 F	6 LB	8.1	30.9	13.8	90.6	TT	0	E11-106R-003522
7.50 - 16 SL	STANDARD	94053308	I1		10	5.50 F	6 LB	8.1	30.9	13.8	90.6	TT	0	E11-106R-004278
9.00 - 16 SL	STANDARD	94049394	I1		10	6 LB	8 LB ; W 8 L	9.2	33.3	14.7	97.5	TL	0	E11-106R-004642
9.00 - 16 SL	STANDARD	94006106	I1		10	6 LB	8 LB ; W 8 L	9.2	33.3	14.7	97.5	TT	0	E11-106R-004642
14L - 16.1 SL	STANDARD	94034000	I1		12	W 11 C		14.2	36.8	16.1	107.9	TL	0	E11-106R-004298

<b>14L - 16.1 SL</b>	STANDARD	94035403	I1		8	W 11 C		14.2	36.8	16.1	107.9	TL	0	E11-106R-004297
<b>16.5L - 16.1 SL</b>	STANDARD	94055128	I1	145 D	14	W 14 C	W 14 CH	17.1	40.4	17.5	118.2	TL	0	E11-106R-007163
<b>16.5L - 16.1 SL</b>	STANDARD	94031337	I1	138 D	10	W 14 C	W 14 CH	17.1	40.4	17.5	118.2	TL	0	E11-106R-003391
<b>19L - 16.1 SL</b>	STANDARD	94032105	I1		10	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	TL	0	E11-106R-004299
<b>19L - 16.1 SL</b>	STANDARD	94035311	I1		14	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	TL	0	E11-106R-006676
<b>19L - 16.1 SL</b>	STANDARD	94041428	I1		12	W 16 C	W 16 CH	19.3	43.3	18.7	126.9	TL	0	E11-106R-004300
<b>21.5L - 16.1 SL</b>	STANDARD	94052738	I1		18	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	TL	0	E11-106R-004301
<b>21.5L - 16.1 SL</b>	STANDARD	94039944	I1		8	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	TL	0	
<b>21.5L - 16.1 SL</b>	STANDARD	94032341	I1		14	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	TL	0	E11-106R-006677
<b>21.5L - 16.1 SL</b>	STUBBLE RESISTANT	94064304	I1	143 D	8	W 18 CH	W 16 CH	22.4	45.3	19.5	138.2	TL	0	E11-106R-006859
<b>10.5/80 - 18</b>	STANDARD	94057146	I1	135 A8	12	W 9	W 8 ; 9	11	35	16.4	105.5	TT	1	
<b>11.25 - 24 SL</b>	STANDARD	94045648	I1		8	W 10 H	W 10 ; W 8	12.8	46.1	0	0	TL	0	E11-106R-004402
<b>9.00 - 24 SL</b>	STUBBLE RESISTANT	94045631	I1		8	W 8 H		10.7	43.1	0	0	TL	0	E11-106R-006674

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:07

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..