

LG 306 - Technical Specifications



Description

LG 306 is a lawn and garden tire suitable for mowers. In some sizes, LG 306 is also fit for small tractors. The specific tread pattern makes the tire gentle on the ground, easing handling at the same time. LG 306 is available in an "aramid-belted" version for users who need strengthened puncture resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower • Small Tractor

Version	ARAMID BELTED
Type	TL
Tyre Size	29 X 12.50 - 15

Dimensions International Standard

Ply Rating	10
Section Width (mm)	318
Overall Diameter (mm)	740
Static Loaded Radius (mm)	349
Rolling Circumference (mm)	2230
Rim Rec	10 LB
ECE	E11-106R-006167

Load capacity (Kg)

km/h / bar	4.1
50	1150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 14:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..