

## LIFT STAR PLUS - Technical Specifications



### Description

LIFT STAR is a bias-ply tire specially designed for telehandlers operating in demanding construction operations and other severe applications. Its low-profile sidewall ensures excellent stability in high-lifting operations whereas its non-directional tread design allows for greater mounting versatility. In addition, the specially designed sidewall provides added cut-and-puncture protection.

### UM

International Standard

### Construction

 BIAS

### Machinery

Industrial: Telehandler

Version	STANDARD
Type	TL
Tyre Size	370/75 - 28

## Dimensions International Standard

Ply Rating	14
Section Width (mm)	365
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	583
Rolling Circumference (mm)	3851
Rim Rec	11.00
ECE	E11-106R-005331

## Load capacity (Kg)

km/h / bar	3.25	5.00
50	3250	-
10	-	5450

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 00:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..