

MULTIMAX SR 261 - Technical Specifications



Description

MULTIMAX SR 261 is an All Steel radial tire with multi-layer steel belts specially designed for Low Platform Trailer, Agri Trailer and Mobile Harbour Crane in transport applications and port operations.

Its strong carcass and special tread compound ensure longer tire life. Thanks to its siped tread design, MULTIMAX SR 261 allows for superior traction in all applications. In addition, the unique 5 RIB tread design maximizes ground contact for even tread wear.

UM

International Standard

Construction

 RADIAL

Machinery

Industrial: Low Platform Trailer • Mobile Crane

Version	STANDARD
Type	TL
Tyre Size	215/75 R 17.5
LI/SS	135/133 J

Dimensions International Standard

Overall Width (mm)	210
Overall Diameter (mm)	775
Static Loaded Radius (mm)	356
Rolling Circumference (mm)	2371
Rim Rec	6.00
Rim Alt	6.75

Load capacity (Kg)

	km/h / bar	8.50
100 Load Single		2180
100 Load Dual		2060

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..