



# MULTIMAX SR 261 - Data Sheet

## Description

MULTIMAX SR 261 is an All Steel radial tire with multi-layer steel belts specially designed for Low Platform Trailer, Agri Trailer and Mobile Harbour Crane in transport applications and port operations.

Its strong carcass and special tread compound ensure longer tire life. Thanks to its siped tread design, MULTIMAX SR 261 allows for superior traction in all applications. In addition, the unique 5 RIB tread design maximizes ground contact for even tread wear.



## UM

International Standard

## Construction

 RADIAL

## Machinery

Industrial: Low Platform Trailer • Mobile Crane

SIZE	Version	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
<b>215/75 R 17.5</b>	STANDARD	135/133 J	6.00	6.75	210	775	356	2371	TL
<b>285/70 R 19.5</b>	STANDARD	150/148 J	8.25	7.50 ; 9.00	280	903	412	2779	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..