

PAC MASTER PLUS - Technical Specifications



Description

PAC MASTER PLUS is a bias tire for compactors. It features high stability and a wider contact area. It is made of a special compound providing high heat resistance. PAC MASTER PLUS ensures an extended tire life-cycle.

UM

US Standard

Construction



Machinery

Industrial: Compactor

Version	STANDARD
Туре	TT
Tyre Size	7.50 - 15

Dimensions US Standard

Usa code	94048809
Ply Rating	14
Section Width (inch)	8.9
Overall Diameter (inch)	31.1
Static Loaded Radius (inch)	14.8
Rolling Circumference (inch)	93.9
Rim Rec	6.0
Rim Alt	6.5
ECE	E11-106R-005322

Load capacity (lbs)

mph / psi	127
5	6400
10	5070

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 15:21

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..