

RIB IMPLEMENT (A) - Data Sheet



Description

RIB IMPLEMENT (A) has been engineered for trailers and implement machinery in transport and soil tillage applications. It is ideal for modern farming and shows top performance both on and off the road. RIB IMPLEMENT (A) is the right choice for all operating conditions which require a high level of handling as well as reduced soil compaction to preserve the crops.

UM

International Standard

Construction



Machinery

Agriculture: Implement Machinery • Trailer

| SIZE | Version | LI/SS FREE ROLLING | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Туре | ECE |
|--------------|----------|--------------------|----|---------|---------|-----|-----|-----|------|------|-----------------|
| 10.0/80 - 12 | STANDARD | 110 A8 | 6 | 9.00 | 7.0 | 264 | 746 | 329 | 2186 | TL | E11-106R-003533 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 12:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..