

RIB TRAILER - Data Sheet



Description

RIB TRAILER is a bias tire specially designed for on & off the road applications with implement machinery, particularly straw reapers.

Its 4-rib design optimizes load distribution, and the strong casing ensures stubble resistance. RIB TRAILER has been designed with a special compound that ensure an excellent tire life thanks to its high wear resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery

| SIZE | Version | LI/SS | PR | RIM REC | RIM ALT | SW | OD | Type |
|-----------|----------|--------|----|---------|-----------------------|-----|-----|------|
| 6.00 - 16 | STANDARD | 94 A6 | 8 | 4.50 E | 4.00 E ; 5 K ; 5.00 F | 170 | 735 | TT |
| 7.00 - 19 | STANDARD | 119 A3 | 10 | 5.00 | | 210 | 875 | TT |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 11:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..