

ROCK STAR IND4 - Data Sheet



Description

ROCK STAR PORT IND-4 has been specifically designed for empty container handlers and forklifts. In addition to excellent traction, the unique tread compound provides superior cut and chip resistance. ROCK STAR PORT IND-4 ensures outstanding load capacity and extraordinary durability.

UM

International Standard

Construction

✚ BIAS

Machinery

Industrial: Empty Container Handler • Forklift

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
14.00 - 24	PORT INDUSTRIAL	IND4	32	10.00 W		390	1425	635	4350	TL
14.00 - 24	PORT INDUSTRIAL	IND4	32	10.00 WA	10.00 VA	390	1425	635	4350	TL
14.00 - 24	PORT INDUSTRIAL	IND4	32	10.00 W		390	1425	635	4350	TT
14.00 - 24	PORT INDUSTRIAL	IND4	32	10.00 WA	10.00 VA	390	1425	635	4350	TT
14.00 - 24	PORT INDUSTRIAL	IND4	28	10.00 W		390	1425	635	4350	TT
14.00 - 24	PORT INDUSTRIAL	IND4	28	10.00 W		390	1425	635	4350	TL
14.00 - 24	PORT INDUSTRIAL	IND4	28	10.00 WA	10.00 VA	390	1425	635	4350	TT
14.00 - 24	PORT INDUSTRIAL	IND4	28	10.00 WA	10.00 VA	390	1425	635	4350	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 02:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..