

SNOW RIDE - PLUS - Technical Specifications



Description

SNOW RIDE - PLUS is particularly suitable for road applications in winter conditions. It features excellent traction and is ideal for ice and snow operations. Its specially designed tread pattern eliminates slippage risks.

UM

International Standard

Construction

 BIAS

Machinery

Industrial: Loader

Version	STANDARD
Type	TL
Tyre Size	23.5 - 25

Dimensions International Standard

Ply Rating	16
Section Width (mm)	600
Overall Diameter (mm)	1630
Static Loaded Radius (mm)	694
Rolling Circumference (mm)	4765
Rim Rec	19.50/2.5
TRA Code	L2

Load capacity (Kg)

km/h / bar	3.00
10	9500

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 03:56

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..