

## SR 713 - Technical Specifications



### Description

SR 713 is an All Steel radial tire with VF technology for farming implements. The tire features a strong multi-ply steel-belted casing and a multi-rib tread pattern ensuring low rolling resistance and a uniform tread wear. Thanks to its large footprint, this VF tire provides reduced soil compaction. SR 713 excels in both performance and reliability offering excellent speed levels even on the road.

### UM

International Standard

### Construction

 RADIAL

### Machinery

Agriculture: Implement Machinery

Version	STANDARD
Type	TL
Tyre Size	VF 385/65 R 22.5
LI/SS	163 D

## Dimensions International Standard

Overall Width (mm)	385
Overall Diameter (mm)	1080
Static Loaded Radius (mm)	487
Rolling Circumference (mm)	3251
Rim Rec	11.75
Rim Alt	12.25
ECE	E11-106R-007881
TRA Code	I1

## Load capacity (Kg)

km/h / bar	2.4	2.6	2.8	3	3.2	3.4	3.6	3.8	4	4.2	4.4	4.6	4.8
0	6440	6900	7245	7705	7935	8395	8915	9200	9775	10065	10640	10925	11215
10	5040	5400	5670	6030	6210	6570	6975	7200	7650	7875	8325	8550	8775
15	4845	5190	5450	5795	5970	6315	6705	6920	7355	7570	8000	8220	8435
25	4425	4740	4975	5295	5450	5765	6125	6320	6715	6915	7310	7505	7705
30	4230	4530	4755	5060	5210	5510	5850	6040	6420	6605	6985	7175	7360
40	3810	4080	4285	4555	4690	4965	5270	5440	5780	5950	6290	6460	6630
50	3390	3630	3810	4055	4175	4415	4690	4840	5145	5295	5595	5750	5900
60	2995	3210	3370	3585	3690	3905	4145	4280	4550	4680	4950	5085	5215
65	2800	3000	3150	3350	3450	3650	3875	4000	4250	4375	4625	4750	4875
70	2550	2730	2865	3050	3140	3320	3525	3640	3870	3980	4210	4325	4435

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 14:04

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..