



## STEER FARM - Data Sheet

### Description

STEER FARM has been designed for 2WD tractors in soil tillage applications, providing excellent steering performance.

### UM

US Standard

### Construction

BIAS

### Machinery

Agriculture: 2WD Tractor



SIZE	Version	USACode	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
5.20 - 14	STANDARD	94046218	F2	75 A6	6	3.50 D	4.00 E	5.3	24.6	11.7	72.3	TT	E11-106R-004092
6.00 - 16	STANDARD	94030842	F2	91 A8	8	4.50 E	4.00 E ; 5 K ; 5.00 F	6.7	29.1	13.9	89.7	TT	E4-106R-002186
6.50 - 16	STANDARD	94043811	F2	90 A8	8	4.50 E	4.00 E ; 5.00 F ; 5.50 F	7.3	30.3	0	0	TT	E4-106R-002187
7.50 - 16	STANDARD	94030859	F2	99 A8	8	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.7	14.9	96.5	TT	E11-106R-003547
7.50 - 16	STANDARD	94065844	F2	105 A8	10	5.50 F	5.00 F ; 5 K ; 6.00 F	8.1	31.7	14.9	96.5	TT	
6.50 - 20	STANDARD	94043736	F2	93 A8	8	5.50 F	4.00 E ; 5.00 F	7.7	34.6	16.5	106.3	TT	E4-106R-002833

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 10:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..