

TR 137 - Technical Specifications



Description

TR 137 is BKT's most suitable tire for all harvesting operations. It ensures excellent traction in the fields even with high loads. The tire is available in different versions: the "aramid-belted" version provides better puncture resistance and protection against all typical damages of this application; the "HD" version provides extraordinary cut and chip resistance, and an extended tire life-cycle.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Harvester

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 24.5 - 32 |
| LI/SS | 156 A8 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94004317 |
| Ply Rating | 12 |
| Section Width (inch) | 24.5 |
| Overall Diameter (inch) | 71.1 |
| Static Loaded Radius (inch) | 31.8 |
| Rolling Circumference (inch) | 210.4 |
| Rim Rec | DW 21 B |
| Rim Alt | DW 20 B |
| ECE | E4-106R-002271 |
| TRA Code | R1 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 24 |
| 25 | 8800 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..