

TR 313 - Technical Specifications



Description

TR 313 is a lawn and garden tire suitable for municipality and soil tillage operations with implement machinery, trenchers and orchard harvesters. The large contact area provides excellent grip. The TR 313 tire has been engineered to ensure a high level of stability also in critical operating conditions along with great self-cleaning properties.

UM

US Standard

Construction

BIAS

Machinery

Agriculture: Implement Machinery • Orchard Harvester • Trencher

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 31 X 15.50 - 15 |

Dimensions US Standard

| | |
|------------------------------|----------------|
| Usa code | 94025589 |
| Ply Rating | 8 |
| Section Width (inch) | 14.6 |
| Overall Diameter (inch) | 30.7 |
| Static Loaded Radius (inch) | 13.5 |
| Rolling Circumference (inch) | 87.9 |
| Rim Rec | 13 LB |
| ECE | E4-106R-002208 |

Load capacity (lbs)

| | |
|-----------|------|
| mph / psi | 45 |
| 30 | 2760 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 00:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..