

TR 459 - Technical Specifications



Description

TR 459 has been particularly designed for digging and loading operations as well as municipality and maintenance applications with tractors and backhoe loaders. It offers high stability and is available in two versions. The "special" version provides an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader • Tractor
Industrial: Backhoe Loader

Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 24
LI/SS	149 A8

Dimensions International Standard

Ply Rating	12
Section Width (mm)	450
Overall Diameter (mm)	1310
Static Loaded Radius (mm)	590
Rolling Circumference (mm)	3850
Rim Rec	DW 15 L
Rim Alt	DW 14 L
ECE	E11-106R-003624
TRA Code	R4

Load capacity (Kg)

km/h / bar	2.60
40	3250

Printed on 04/07/2024 17:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..