

TR 882 - Technical Specifications



Description

TR 882 is a very versatile tire suitable for several applications and vehicles. It has been designed to fit implement machinery, hay harvesters/balers and sugar cane machinery. Engineered with a special compound to reduce damage, this tire features also great durability and traction in every field condition. TR 882 is also available as "aramid-belted", "HD" and "special" versions to meet specific end user requirements.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Implement Machinery
• Trailer
Industrial: Trailer

Version	STANDARD
Type	TL
Tyre Size	400/60 - 15.5
LI/SS DRIVE WHEEL	132 A8
LI/SS FREE ROLLING	145 A8

Dimensions US Standard

Usa code	94019861
Ply Rating	14
Section Width (inch)	15.7
Overall Diameter (inch)	34.4
Static Loaded Radius (inch)	14.9
Rolling Circumference (inch)	102.6
Rim Rec	AG 13.00
ECE	E4-106R-001879

Load capacity (lbs)

mph / psi	52
5 FR	8950
15 FR	7610
20 FR	7160
25 FR	6390
5 DW	6170
15 DW	5250
20 DW	4940
25 DW	4410

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 22/11/2024 01:53

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..