



## EARTHMAX SR 315 CS - Ficha técnica



### Description

EARTHMAX SR 315 CS L-3S es un neumático radial All Steel diseñado especialmente para los ejes delanteros de las cargadoras con cadenas en operaciones mineras. El contorno especial de la banda de rodadura con un hombro biselado (CS) permite que las cadenas de los neumáticos se ajusten mejor a lo largo de la superficie de la banda de rodadura, incluida la zona del hombro. Su diámetro total tras la aplicación de la cadena coincide con el del BKT EARTHMAX SR 55 L-5S instalada en el eje trasero, para que los neumáticos delanteros y traseros coincidan. EARTHMAX SR 315 CS se ha diseñado para eliminar el riesgo de daños en los neumáticos delanteros durante las operaciones de excavación con LHD (volquete rígido subterráneo) y cargadoras.

### UM

US Standard

### Construction

RADIAL

### Machinery

OTR: Cargadora LHD • Pala cargadora

| SIZE              | Version                | USACode  | TRA Code | Star R | LI/SS  | RIM REC   | RIM ALT   | OW   | OD   | SLR  | RC    | Type |
|-------------------|------------------------|----------|----------|--------|--------|-----------|-----------|------|------|------|-------|------|
| <b>29.5 R 29</b>  | CUT RESISTANT COMPOUND | 94069378 | L3S      | **     | 218 A2 | 25.00/3.5 | 24.00/3.5 | 30.7 | 74.4 | 33.1 | 225   | TL   |
| <b>35/65 R 33</b> | CUT RESISTANT COMPOUND | 94070992 | L3S      | ***    | 229 A2 | 28.00/3.5 | -         | 34.6 | 76.7 | 34.1 | 231.7 | TL   |
| <b>35/65 R 33</b> | CUT RESISTANT COMPOUND | 94069385 | L3S      | **     | 224 A2 | 28.00/3.5 | -         | 34.6 | 76.7 | 34.1 | 231.7 | TL   |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 05/11/2024 6:03

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..