

AGRIMAX ELOS - Especificaciones técnicas



Description

AGRIMAX ELOS ha sido proyectado para ofrecer la máxima tracción en condiciones de uso particularmente problemáticas en terrenos mojados - como por ejemplo los arrozales - y pantanosos. El dibujo de la banda de rodadura ha sido estudiado para garantizar óptimas cualidades de auto-limpieza, esenciales en los trabajos realizados en terrenos fangosos y durante los desplazamientos. Para optimizar la productividad de la empresa agrícola, en el dibujo del neumático AGRIMAX ELOS se han integrado unas protecciones en los flancos para asegurar la máxima protección ante posibles daños.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Tractor

Version	STANDARD
Type	TL
Tyre Size	480/70 R 34
LI/SS	155 A8/155 B

Dimensions International Standard

Section Width (mm)	500
Overall Diameter (mm)	1605
Static Loaded Radius (mm)	733
Rolling Circumference (mm)	4868
SRI (mm)	750
Rim Rec	W 15 L
Rim Alt	W 16 L ; W 14 L
ECE	E11-106R-007532
TRA Code	R2

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4	2.8	3.2
50	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
40	1515	1785	2055	2290	2560	2790	3065	3375	3645	3875
30	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150
10 LT	2030	2390	2755	3070	3430	3745	4105	4520	4885	5195
10 HT	1620	1910	2200	2450	2740	2990	3280	3615	3905	4150

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 16:54

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..