

## AGRIMAX FORTIS - Especificaciones técnicas



### Description

AGRIMAX FORTIS es vuestro compañero más fiable para todas las operaciones de preparación y tratamiento del terreno y de transporte. Diseñado para equipar los tractores más potentes de última generación, AGRIMAX FORTIS permite transportar cargas muy elevadas con velocidades hasta 65 km/h. Asegura una tracción excelente además de una duración superior y un gran confort para una experiencia perfecta de conducción. El neumático ha sido desarrollado con una carcasa reforzada de nylon que mejora la productividad en los campos y preserva el suelo gracias a una menor compactación.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Tractor

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 600/70 R 34  |
| LI/SS     | 160 D/163 A8 |

## Dimensions US Standard

|                              |                  |
|------------------------------|------------------|
| Usa code                     | 94035649         |
| Section Width (inch)         | 23.3             |
| Overall Diameter (inch)      | 67.1             |
| Static Loaded Radius (inch)  | 30               |
| Rolling Circumference (inch) | 201.1            |
| Rim Rec                      | DW 18 L          |
| Rim Alt                      | DW 20 B ; W 18 L |
| ECE                          | E4-106R-001401   |
| TRA Code                     | R1W              |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17   | 20    | 23    | 29    | 35    |
|-----------|------|------|------|------|-------|-------|-------|-------|
| 40        | 4760 | 5560 | 6250 | 6940 | 7640  | 8230  | 9130  | 9920  |
| 30        | 5000 | 5840 | 6570 | 7300 | 8020  | 8650  | 9590  | 10420 |
| 25        | 5160 | 6020 | 6780 | 7530 | 8280  | 8930  | 9890  | 10750 |
| 20        | 5480 | 6390 | 7200 | 7990 | 8780  | 9480  | 10500 | 11410 |
| 5 LT      | 6380 | 7450 | 8380 | 9310 | 10240 | 11030 | 12230 | 13290 |
| 5 HT      | 5480 | 6390 | 7200 | 7990 | 8780  | 9480  | 10500 | 11410 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 17:11

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..