

## AGRIMAX RT 600 - Ficha técnica

### Description

AGRIMAX RT 600 es el neumático ideal para utilizarlo en cubiertas herbáceas y actividades de cosecha y pulverización. Gracias a su amplia área de contacto, AGRIMAX RT 600 garantiza una óptima distribución de la presión sobre el terreno reduciendo los daños de prados y protege el suelo. Gracias a la tecnología con hombro redundado, la banda de rodamiento reforzada y el número mayor de tacos, el neumático asegura una grande estabilidad y excelente tracción.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agricultura: Cosechadora • Esparcidor • Tractor



| SIZE                                | Version      | USACode  | LI/SS        | RIM REC                | RIM ALT           | SW   | OD   | SLR  | RC    | Type | ECE             |
|-------------------------------------|--------------|----------|--------------|------------------------|-------------------|------|------|------|-------|------|-----------------|
| <b>620/75 R 26<br/>(23.1 R 26)</b>  | STANDARD     | 94050444 | 167 A8/B     | DW 20 B                |                   | 24.6 | 62.6 | 28.7 | 191   | TL   | E11-106R-002993 |
| <b>750/65 R 26</b>                  | STANDARD     | 94064311 | 171 A8/B     | DW 24 B                | DW 23 B ; DW 25 B | 29.5 | 64.4 | 29   | 196.3 | TL   | E11-106R-006182 |
| <b>750/70 R 26</b>                  | STANDARD     | 94073146 | 172 A8/B     | DW 25 B                | DW 24 B           | 30.7 | 68.9 | 30.9 | 207.4 | TL   | E11-106R-007934 |
| <b>540/65 R 28</b>                  | STANDARD     | 94053704 | 142 D/145 A8 | W 16 L                 | W 18 L            | 20.9 | 55.6 | 25.3 | 165.4 | TL   | E11-106R-002980 |
| <b>1050/50 R32</b>                  | STANDARD     | 94040728 | 184 A8/181 B | 36.0 VA                |                   | 41.7 | 73.3 | 32.5 | 224.4 | TL   | E4-106R-000813  |
| <b>650/75 R 32</b>                  | STANDARD     | 94055968 | 172 A8/B     | DW 21 B                | DW 20 B ; DW 23 B | 25.8 | 70.4 | 31.8 | 213.2 | TL   | E11-106R-004755 |
| <b>800/65 R 32<br/>(30.5L R 32)</b> | STANDARD     | 94044795 | 176 A8/173 B | DW 27 B                | DH 27 B ; DW 25 B | 30.5 | 71.7 | 32.4 | 218.8 | TL   | E4-106R-001428  |
| <b>800/65 R 32<br/>(30.5L R 32)</b> | STANDARD     | 94039302 | 181 A8/178 B | DW 27 B                | DH 27 B ; DW 25 B | 30.5 | 71.7 | 32.4 | 218.8 | TL   | E4-106R-001429  |
| <b>900/60 R 32</b>                  | STANDARD     | 94062423 | 181 A8/178 B | DW 27 B                | DW 28 B ; DW 30 B | 35.3 | 74.5 | 33.1 | 224.3 | TL   | E11-106R-005768 |
| <b>IF 1250/50 R 32<br/>CFO</b>      | STEEL BELTED | 94070763 | 201 B        | VA44/1.7 (multipiece)  |                   | 49.1 | 81.2 | 35.3 | 241.6 | TL   | E11-106R-006958 |
| <b>IF 1250/50 R 32<br/>CFO</b>      | STEEL BELTED | 94068876 | 201 B        | DH44B/1.3 (multipiece) |                   | 49.1 | 81.2 | 35.3 | 241.6 | TL   | E11-106R-006958 |
| <b>IF 680/85 R 32<br/>CFO</b>       | STANDARD     | 94065486 | 179 D        | DW23 B                 | DW21 B            | 26.9 | 77.2 | 33.3 | 230.7 | TL   | E11-106R-006401 |
| <b>650/65 R 38</b>                  | STANDARD     | 94053667 | 157 D/160 A8 | DW 20 B                |                   | 25.4 | 71.3 | 32.8 | 214.3 | TL   | E11-106R-002990 |
| <b>710/70 R 38</b>                  | STANDARD     | 94063420 | 178 D/181 A8 | DW 23 B                | DW 25 B           | 27.8 | 77.1 | 34.7 | 233.3 | TL   | E11-106R-006178 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/11/2024 12:48

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..