

## AGRIMAX RT 657 - Especificaciones técnicas



### Description

AGRIMAX RT 657 es el neumático ideal para utilizarlo tanto en el laboreo del suelo como por la carretera; además algunos tamaños también son adecuados para la vendimia. Este neumático asegura un excelente confort en la conducción, así como significativos ahorros de carburante. Presenta una elevada capacidad de carga a altas velocidades. AGRIMAX RT 657 es la mejor elección para quien necesite un neumático versátil y fiable sin comprometer las prestaciones.

### UM

US Standard

### Construction

RADIAL

### Machinery

Agricultura: Tractor • Vendimiadora

|           |              |
|-----------|--------------|
| Version   | STANDARD     |
| Type      | TL           |
| Tyre Size | 650/65 R 42  |
| LI/SS     | 165 D/168 A8 |

## Dimensions US Standard

|                              |                   |
|------------------------------|-------------------|
| Usa code                     | 94029501          |
| Section Width (inch)         | 25.4              |
| Overall Diameter (inch)      | 75.3              |
| Static Loaded Radius (inch)  | 34.6              |
| Rolling Circumference (inch) | 228.7             |
| Rim Rec                      | DW 20 B           |
| Rim Alt                      | DW 21 B ; DW 23 B |
| ECE                          | E4-106R-000625    |
| TRA Code                     | R1W               |

## Load capacity (lbs)

| mph / psi | 9    | 12   | 15   | 17    | 20    | 23    | 29    | 35    |
|-----------|------|------|------|-------|-------|-------|-------|-------|
| 40        | 5460 | 6360 | 7150 | 7950  | 8750  | 9420  | 10450 | 11400 |
| 30        | 5730 | 6680 | 7520 | 8360  | 9190  | 9910  | 10980 | 11930 |
| 25        | 5930 | 6920 | 7780 | 8640  | 9510  | 10250 | 11360 | 12350 |
| 20        | 6270 | 7320 | 8230 | 9150  | 10060 | 10850 | 12030 | 13060 |
| 5 LT      | 7310 | 8530 | 9600 | 10660 | 11730 | 12640 | 14010 | 15220 |
| 5 HT      | 6270 | 7320 | 8230 | 9150  | 10060 | 10850 | 12030 | 13060 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 02/11/2024 23:24

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..