

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	250/85 R 28 (9.5 R 28)
LI/SS	112 A8/B

Dimensions US Standard

Usa code	94037520
Section Width (inch)	9.9
Overall Diameter (inch)	44.8
Static Loaded Radius (inch)	20.4
Rolling Circumference (inch)	134.7
Rim Rec	W 8
Rim Alt	W 7 ; W 9
ECE	E4-106R-000646
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	1370	1590	1810	2030	2250	2470
25	1370	1590	1810	2030	2250	2470
20	1450	1700	1940	2170	2410	2650
5 LT	1830	2130	2420	2720	3020	3320
5 HT	1450	1700	1940	2170	2410	2650

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 15:58

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..