

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	STANDARD
Type	TL
Tyre Size	320/85 R 24 (12.4 R 24)
LI/SS	122 A8/B

Dimensions International Standard

Section Width (mm)	329
Overall Diameter (mm)	1154
Static Loaded Radius (mm)	519
Rolling Circumference (mm)	3424
SRI (mm)	550
Rim Rec	W 11
Rim Alt	W 9 ; W 10
ECE	E4-106R-000613
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	825	960	1095	1230	1365	1500
40	825	960	1095	1230	1365	1500
30	885	1030	1175	1320	1465	1605
10 LT	1110	1290	1470	1650	1830	2010
10 HT	885	1030	1175	1320	1465	1605

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 13:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..