

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

International Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	420/85 R 30 (16.9 R 30)
LI/SS	140 A8/B

Dimensions International Standard

Section Width (mm)	438
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	661
Rolling Circumference (mm)	4421
SRI (mm)	700
Rim Rec	W 15 L
Rim Alt	W 13 ; W 14 L
ECE	E4-106R-000654
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	1375	1600	1825	2050	2275	2500
40	1375	1600	1825	2050	2275	2500
30	1475	1715	1955	2195	2435	2675
10 LT	1845	2145	2450	2750	3050	3350
10 HT	1475	1715	1955	2195	2435	2675

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 23/11/2024 17:06

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..