

AGRIMAX RT 855 - Especificaciones técnicas



Description

AGRIMAX RT 855 es un neumático que se distingue por su excelente tracción y confort. Ha sido desarrollado principalmente para el laboreo del suelo y el transporte tanto en el campo como por la carretera; algunos tamaños son adecuados también para las actividades de pulverización y de vendimia. AGRIMAX RT 855 posee óptimas características de auto-limpieza que permiten cambiar rápidamente su uso del campo a la carretera.

UM

US Standard

Construction

 RADIAL

Machinery

Agricultura: Pulverizador • Tractor • Vendimiadora

Version	SPECIAL
Type	TL
Tyre Size	520/85 R 46
LI/SS	158 A8/B

Dimensions US Standard

Usa code	94062072
TMPH	1
Section Width (inch)	20.3
Overall Diameter (inch)	80.8
Static Loaded Radius (inch)	36.6
Rolling Circumference (inch)	242.4
Rim Rec	DW 16 L ; W 16 A ; W 16 L ; DD 16
Rim Alt	DW 18 L ; W 18 L ; W 18 A
ECE	E4-106R-001415
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23
30	5160	6000	6840	7680	8530	9370
25	5160	6000	6840	7680	8530	9370
20	5520	6430	7330	8230	9140	10030
5 LT	6910	8040	9170	10300	11430	12550
5 HT	5520	6430	7330	8230	9140	10030

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 24/11/2024 0:09

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..